



High Protection Level IP65 Indoor & outdoor options



Various Mounting Methods Wall-mounted or floor-standing installation



Higher Level Safety LFP & Smart BMS



Stronger Scalability 2-8 units can be used in parallel



Longer Life Time Long cycle life and superior performance



Wider Compatibility Compatible with Top inverter brands











Specification PACK G1 5.0

Model	PACK G1-5.0
Battery Module Type	LiFePO4
Nominal Battery Energy (KWH)	5.12
Nominal Capacity (AH)	100
Nominal Voltage (V)	51.2
Usable Energy (KWH)	4.096
Voltage Range (V)	40~58.4
Recommended Charge & Discharge C	Rate 0.5C
Recommend Charge/ Discharge Current (A)	50
Max Charge/ Discharge Current(A)	100
Dimensions (W*D*H,mm)	458*197*610
Net Weight (kg)	54
Communication	RS485/RS232/CAN
Working Temperature	0℃~50℃ Charge -10℃~50℃ Discharge
Shelf Temperature	-20°C~60°C
Protection Level	IP65
Expansion	Up to 8 units in parallel
Certification	CE/IEC/UL/UN38.3/MSDS
Design Life	10 years+
Cycle Life	>6000
Warranty	10 years
Compatible Inverters	SMA/Victron/Megarevo/Delios/Goodwe/Solis/Deye/SAJ/Voltronic/SRNE etc.