



High Protection Level IP65 Indoor & outdoor options



Easier Mounting Method Floor-standing installation with wheels



Higher Level Safety LFP & Smart BMS



Stronger Scalability 2-5 units can be used in parallel



Longer Life Time Long cycle life and superior performance



Wider Compatibility Compatible with Top inverter brands











Specification PACK G2 15.0

Model	PACK G2-15.0
Battery Module Type	LiFePO4
Nominal Battery Energy (KWH)	14.336
Nominal Capacity (AH)	280
Nominal Voltage (V)	51.2
Voltage Range (V)	40~58.4
Recommend Charge/ Discharge Current (A)	100
Max Charge/ Discharge Current(A)	200
Dimensions (W*D*H,mm)	580*278*900
Net Weight (kg)	115
Communication	RS485/RS232/CAN
Working Temperature	0℃~50℃ Charge - 10℃~50℃ Discharge
Shelf Temperature	-20°C~60°C
Protection Level	IP65
Expansion	Up to 5 units in parallel
Certification	CE/IEC/UL/UN38.3/MSDS
Design Life	10 years+
Cycle Life	>6000
Warranty	10 years
Compatible Inverters	SMA/Victron/Megarevo/Delios/Goodwe/Solis/Deye/SAJ/Voltronic/SRNE etc.